




**CAP & PIN REPLACEMENT INSULATORS**  
**RG® Resistive Graded Glaze Reference**

Type	T.R.	Height (in.)	Section Qty.	Catalog	Catalog	Cantilever Strength		Tension	Torsion	Compression	
				Number Standard Glaze (Light Grey)	Number RG® Glaze	(lbs.) Upright	(lbs.) Underhung	Strength (lbs.)	Strength (lbs.)	Strength (lbs.)	
	4	10	1	315205-70	535205A	110	2000	2000	8500	7000	10000
	44	10	1	315044-70	535044A	110	4000	4000	15000	14000	20000
	7	12	1	315007-70	535007A	150	2000	2000	5000	8000	10000
	46	12	1	315046-70	535046A	150	4000	4000	20000	16000	20000
	10	15	1	315010-70	535010A	200	2000	2000	7000	10000	15000
	49	15	1	315049-70	535049A	200	4000	4000	20000	20000	30000
	13	18	1	315013-70	535013A	250	2000	2000	8000	12000	15000
	53	20	1	315053-70	535053A	250	4000	4000	15000	20000	30000
	16	29	1	315016-70	535016A	350	1500	1500	12000	15000	25000
	56	29	1	315056-70	535056A	350	3000	3000	25000	40000	60000
	19	43.5	1	315019-70	535019A	550	1700	1700	20000	60000	60000
	173	43.5	1	315173-70	535173A	550	2900	2900	25000	90000	90000
	25	58	1	315025-70	535025A	750	1200	1070	20000	40000	60000
	174	58	1	315174-70	535174A	750	2000	1750	25000	90000	75000
	126	72.5	2	315126-70	535126A	900	910	910	20000	40000	60000
	175	72.5	2	315175-70	535175A	900	1450	1450	25000	90000	75000
	128	87	2	315128-70	535128A	1050	750	700	20000	40000	60000
176	87	2	315176-70	535176A	1050	1170	1100	25000	90000	75000	
	4	10	1	317004-70	317004A	110	2000	1000	5000	7000	10000
	44	10	1	317044-70	317044A	110	4000	3000	10000	14000	20000
	7	12	1	317007-70	317007A	150	2000	1000	5000	8000	10000
	46	12	1	317046-70	317046A	150	4000	3000	10000	16000	20000
	10	15	1	317010-70	317010A	200	2000	1000	7000	10000	15000
	49	15	1	317049-70	317049A	200	4000	3000	14000	20000	30000
	13	18	1	317013-70	317013A	250	2000	1000	8000	12000	15000
	53	20	1	317053-70	317053A	250	4000	2500	20000	40000	60000
	16	29	1	317016-70	317016A	350	1500	1000	12000	15000	25000
	56	29	1	317056-70	317056A	350	3000	2350	20000	40000	60000
	19	43.5	1	317019-70	317017A	550	1700	1470	20000	40000	60000
	173	43.5	1	317173-70	317173A	550	2900	2350	20000	40000	60000
	25	58	1	317025-70	317025A	750	1700	1470	20000	40000	60000
	174	58	1	317174-70	317174A	750	2000	1750	25000	90000	75000
	126	72.5	2	317126-70	317126A	900	910	840	20000	40000	60000
	175	72.5	2	317175-70	317175A	900	1450	1350	25000	90000	75000
	128	87	2	317128-70	317128A	1050	750	700	20000	40000	60000
176	87	2	317176-70	317176A	1050	1170	1100	25000	90000	75000	

**CAP & PIN REPLACEMENT INSULATORS**  
**RG® Resistive Graded Glaze Reference**

	Type	T.R.	Height (in.)	Section Qty.	Catalog	Catalog	Cantilever Strength		Tension	Torsion	Compression	
					Number	Number	(lbs.)		Strength	Strength	Strength	
					Standard Glaze (Light Grey)	RG® Glaze	BIL (kV)	Upright	Underhung	(lbs.)	(lbs.)	(lbs.)
		140	14.5	1	319140-70	539140	210	7000	4000	20000	40000	60000
		139	14.5	1	319139-70	539139	210	10000	6000	25000	90000	75000
		56	29	2	319056-70	539056	350	3000	2350	20000	40000	60000
	Special	29	2	314982-70	534982	350	4500	3500	20000	40000	60000	
		19	43.5	3	319019-70	539019	550	1700	1470	20000	40000	60000
		173	43.5	3	319173-70	539173	550	2900	2400	25000	90000	75000
		25	58	4	319025-70	539025	750	1200	1070	20000	40000	60000
		174	58	4	319174-70	539174	750	2000	1750	25000	90000	75000
		126	72.5	5	319126-70	539126	900	910	840	20000	40000	60000
		175	72.5	5	319175-70	539175	900	1450	1350	25000	90000	75000
		128	87	6	319128-70	539128	1050	750	700	20000	40000	60000
		176	87	6	319176-70	539176	1050	1170	1100	25000	90000	75000

Standard glaze offered in light grey or brown  
 RG® Resistive graded glaze offered in grey only  
 Offered in accordance to ANSI and CSA standard  
 Contact your local manufactureres representative for custom and high leakage designs